

SNE Photovoltaic Modules

M6-48 Series 200W-225W



- POWER RANGE**
 Plus-Sorting 0 ~ + 4,99Wp
- PID RESISTANT**
 Potential induced degradation free
- SALT MIST CORROSION RESISTANT**
 Certified for salt rich environment
- SAND RESISTANT**
 Certified for sand rich environment
- AMMONIA RESISTANT**
 Certified for ammonia rich environment
- HIGH STRENGTHENED DESIGN**
 Maximum mechanical load 5400 Pa
- IP67 JUNCTION BOX**
 Advanced water and dust proof level


HIGH QUALITY
 Our solar photovoltaic modules are characterized by high-quality materials, best workmanship, 1st class development and management.

LINEAR PERFORMANCE GUARANTEE
 With the linear performance guarantee of 30 years and a product warranty of 12 years, SNE Solar guarantees highest investment security and warranty claims.

PLUS-SORTING
 Higher yield due to plus-sorting of 0 to +4.99 Wp guarantees the highest system efficiency and yield stability.

CERTIFICATES
 Our solar photovoltaic modules are not only in line with international standards, but also tested and certified under extreme stress and any environmental influences.

OUR PERFORMANCE GUARANTEE



IEC 61215
IEC 61730
PERIODICAL
INCEPTION



IEC 61215
IEC 61730
PERIODICAL
INCEPTION



Solare New Energy
Technology Co., Ltd.

Tel.: +86 139 2199 5698
Fax: +86 512 5851 6227

E-Mail: info@solarepv.com
Web : www.solarepv.com

ELECTRICAL DATA		SNE200M6-48	SNE205M6-48	SNE210M6-48	SNE215M6-48	SNE220M6-48	SNE225M6-48
Nominal power	Pm (Wp)	200	205	210	215	220	225
Open circuit voltage	Voc (V)	30.34	30.53	30.62	30.74	31.65	31.82
Short-circuit current	Isc (A)	8.81	8.88	8.94	8.98	9.01	9.07
Voltage at max power	Vmp (V)	25.30	25.58	25.84	25.97	26.12	26.35
Current at max power	Imp (A)	7.91	8.01	8.13	8.28	8.42	8.54
Module efficiency	(%)	15.27	15.66	16.04	16.42	16.80	17.18
Cells efficiency	(%)	17.61	18.05	18.49	18.94	19.38	19.82
System Voltage	(V)	1000					
Temp. coefficient Voc	(% / °C)	-0.36					
Temp. coefficient Isc	(% / °C)	0.06					
Temp. coefficient Pm	(% / °C)	-0.36					
Operating temp.	(°C)	-40 bis +85					
NOCT	(°C)	45±2					

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.

TECHNICAL DATA

Junction box	3 bypass diodes, IP67
Wire cross section (Ø, mm ²)	4.0
Cable lenght (mm)	900
Connector type	MC4/MC4 compatible
Dimensions (L x W x H, mm)	1320 x 992 x 35
Weight (kg)	10.8
Cell dimensions (mm)	156 x 156
No of cells / assembly	48 / 6 x 8
Type of cells	mono-crystalline
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400Pa / 244kg / m ²
Mechanical load	5400Pa / 550kg / m ²

SCALE

